

# NMT-244/12C2D1 / NMT-244/12C2D2

12V Class II Dimmable Hardwire Magnetic LED Driver with Breakers

Source: 120V or 277V Input / 12V Output  
240W (4 x 60W Breakers)

Type

Project

Catalog No.

Notes

## PRODUCT DESCRIPTION

12V enclosed dimmable driver to be used with Nora Lighting's 12 Volt systems requiring a Class II driver. Four breakers each produce 60 watts and can be dimmed with low voltage magnetic dimmer. Includes a regulator to provide constant current and constant voltage.

## FEATURES

- Low voltage magnetic dimming
- Integral regulator for constant current and voltage
- Manual Reset Overload Protection for each Class II Circuit
- Indoor/Outdoor Enclosure Type 3R Enclosure
- Conduit Access Wiring Compartment
- Made in USA
- Meets Class II output limits
- 12 Volt DC Rated output
- UL Recognized
- Available in 120V or 277V

## ELECTRICAL

**Input Voltage:** 120V or 277V (must specify)

**Output Voltage:** 12VDC, 5A per circuit max.

**Wattage:** 4 x 60W

**Dimming:** Magnetic Low Voltage

**Regulator:** Constant Current and Constant Voltage

## COMPATIBLE NORA 12V SYSTEMS

LED Drivers are compatible with Nora Lighting's 12V systems

SERIES	DESCRIPTION
<a href="#">NUTP4</a>	12V Standard Tape Light
<a href="#">NUTP6</a>	12V RGB Color Changing Tape Light
<a href="#">NMP-A</a>	12V Josh Adjustable Puck Light
<a href="#">NMP-LED</a>	12V Josh Fixed Puck Light
<a href="#">NMI-170</a>	12V 1" M1 Series

## OPTIONAL ACCESSORIES

**NALTL-10:** 10' Power Line Connector

**NALTL-30:** 30' Power Line Connector


**NATL-302W:** Power Line Splitter, white cable. Splits power line connector into two separate connections.

## LABELS AND LISTINGS

- [3-Year Limited Warranty](#)
- cULus Recognized Driver



## PRODUCT IMAGES & DIMENSIONS



**NMT-244/12C2D1 / NMT-244/12C2D2**  
12V Class II Dimmable Hardwire Magnetic LED Driver



**NALTL-10 / NALTL-30**  
Power Line Connector



**NATL-302W**  
Power Line Splitter

## 12V Class II Dimmable Hardwire Magnetic LED Driver with Breakers

Input Voltage / Output Voltage

**NMT-244/12C2D1** = 120V input / 12V output

**NMT-244/12C2D2** = 277V input / 12V output

## Optional Accessories

Description

**NALTL-10** = 10' Power Line Connector

**NALTL-30** = 30' Power Line Connector

**NATL-302W** = Power Line Splitter, White

Example: **NMT-244/12C2D2** = 277V/12V 240W Class II Dimmable Hardwire Magnetic LED Driver with (4) 60W Breakers