

# Olson

Ceiling Mounted • Dry Location Listed

## Description:

The 52 in Olson five-blade ceiling fan features a generously sized etched watermark glass shade and sweeping blades highlighted with metal accents. Two 9W LED lamps are JA8 compliant, offering both form and function with energy and cost-savings benefits. Olson features a dual mount system and a three-speed pull chain fan switch, as well as an on/off pull chain switch to operate the light. Graphite finish.

## Specifications:

- White Opal glass Bowl
- 52" Olson Collection ceiling fan features five generously sized sweeping reversible blades
- Reversible Walnut and Graphite blades
- Graphite finish
- Features a dual mount system and a three-speed pull chain fan switch, as well as an on/off pull chain switch to operate the light
- Pull chain is chrome
- Add an accessory wall or remote control for added convenience
- Indoor ceiling fan ideal for use in great rooms, living rooms, bedrooms and bonus rooms
- Ceiling fan adds form and function – by providing increased air circulation in rooms
- Features Transitional design styling
- Powerful and reversible 3-speed motor with triple-capacitor control
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- Light kit features white opal glass
- Two 9W LED lamps are JA8 compliant, offering both form and function with energy and cost-savings benefits
- UL/CUL dry location listed
- Dual ceiling mounting on downrod, or close to ceiling
- A 3/4" x 6" downrod is included. Longer accessory downrods can be ordered separately
- Airflow: CFM\*
- Energy consumption: 67 watts\*
- Airflow efficiency: 91 cfm/watt\*
- \* Fan on a downrod
- Fully dimmable with dimmable bulbs.
- Canopy covers a standard 4" recessed outlet box
- Mounting bracket for outlet box included
- 80 in of wire supplied

## Performance:

|                     |                                    |
|---------------------|------------------------------------|
| Number of Lamps     | 2                                  |
| Input Power         | 9 W                                |
| Input Voltage       | 120 V                              |
| Input Frequency     | 60 Hz                              |
| Lumens/LPW (Source) | 800/88 (LM-82)                     |
| CCT                 | 3000 K                             |
| CRI                 | 90 CRI                             |
| Life (hours)        | 25000 (L70/TM-21)                  |
| Warranty            | Limited Lifetime warranty          |
| Labels              | cULus Dry Location Listed          |
|                     | Meets California Title 24 JA8-2016 |
|                     | AC motor                           |

# P2598-143



## Dimensions:

Diameter: 52 in  
 Height: 21-3/8 in

White Opal glass Bowl  
 Width: 11 in  
 Height: 5-1/8 in

## ENERGYGUIDE

Estimated  
Yearly Energy Cost

# \$12

\$3

\$34

Cost Range of Similar Models (19" – 84")

• Based on 12 cents per kWh and 6.4 hours use per day  
 • Your cost depends on rates and use  
 • Energy Use: 42 Watts

Airflow

# 3,458

Cubic Feet Per Minute

• The higher the airflow, the more air the fan will move  
 • Airflow Efficiency: 83 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights ftc.gov/energy

# P2598-143

**Dimming Notes:**

---

P2598-143 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls:**

---

Lutron\_Diva DVELV-300P

Lutron\_Nova T NTELV-300

Lutron\_Maestro MAELV-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.