

# Kaysville

 Ceiling Mounted • Damp Location Listed **PROGRESS LED**

## Description:

Kaysville Collection 6-Blade Chestnut 56-Inch DC Motor LED Urban Industrial Ceiling Fan

## Specifications:

- White Opal Glass Bowl
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 6.5 in W., 2.5 in ht., 6.5 in depth
- 80 in of wire supplied

## Performance:

|                        |  |
|------------------------|--|
| Number of Modules      | 1  |
| Input Power            | 24 W   |
| Input Voltage          | 120 V  |
| Input Frequency        | 60 Hz  |
| Lumens/LPW (Delivered) | 2,100  |
| CCT                    | 3000 K   |
| CRI                    | 90 CRI   |
| Life (hours)           | 50000 (L70/TM-21)  |
| EMI/RFI                | FCC Title 47, Part 15, Class B   |
| Warranty               | Limited Lifetime Warranty  |
| Labels                 | cULus Damp Location Listed<br>Meets California Title 24 JA8-2016<br>DC motor |

# P250003-081-30



## Dimensions:

Length: 56 in  
 Diameter: 56 in  
 Height: 17-1/4 in

White Opal Glass Bowl  
 Width: 8-1/2 in  
 Height: 3-1/8 in

# P250003-081-30

## Dimming Notes:

---

P250003-081-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## Dimming Controls:

---

IDevices IDEV009

Lutron NTEVL-300

Lutron DVELV-300P

Lutron TGCL-153-PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.