ASSEMBLY INSTRUCTIONS

ITEM DESCRIPTION:

ITEM NO.: DMI11 NAME: Everglades Chandelier

MATERIAL TYPE: BRASS FINISH: Antique Brass

SOCKET TYPE: E12 SOCKET QTY: 3

BULB WATTAGE: 40 W/10W CFL/9W LED

VOLTAGE: 110-120 V ITEM NET WEIGHT: 8.82 LBS



TO ASSEMBLE:

- 1. Shut off the main electrical supply from the main fuse box/circuit breaker.
- 2. Carefully unpack all fixture parts and hardware and lay them on a soft surface for assembly.
- 3. Gently pull wiring down from ceiling junction box and allow to hang.
- 4. Remove mounting plate from the canopy by unscrewing the collar.
- 5. Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire nut and wrap the connection with electrical tape.
- 6. Attach the neutral fixture wire from the pendant to the neutral junctionbox wire (usually white). Fasten each together with a wire nut and wrap the connection with electrical tape.
- Attach the hot fixture wire from the pendant to the hot junction box wire (usually black). Fasten each together with a wire nut and wrap the connection with electrical tape.
- DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
- 8. Gently tuck the wire connections neatly into the ceiling junction box.
- $9. \ \mbox{Place}$ the mounting plate over the center of the ceiling junction box.
- 10. Align holes in mounting plate with holes in junction box and attach with two mounting bolts. Secure bolts with a Phillips head screwdriver.
- 11. Push canopy up over the mounting plate until it is flush with the ceiling.
- 12. Push collar through hole in canopy and thread onto nipple on the mounting plate. Secure by turning collar clockwise until canopy is flush with the ceiling.
- 13. Restore power to junction box and test fixture. Insert 3 40W bulbs into fixture. DO NOT EXCEED SPECIFIED WATTAGE OF PENDANT.

PARTS INCLUDED:

Pipes	Qty:- (1) 3",(1) 6" & (2) 12"	
Loop	Qty: 1	
Canopy	Qty: 1	
Mounting Plate	Qty: 1	

HARDWARE INCLUDED:

Mounting Screws	2
Plastic Wire Connector	2
Green Ground Screw	1

TO INSTALL YOU WILL NEED:

- 2 people recommended Phillips Screwdriver
- These instructions are provided for safety. It is very important that they are read carefully and completely before beginning installation.

We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.

CARE INSTRUCTIONS:

Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.

For customer service questions call 1-800-338-2150

ARTERIORS