

Clean, modern design and outstanding light performance distinguish Taag high output LED wall packs. Designed for outdoor security and general illumination, Taag 6 is ideal in commercial and residential applications for which well-defined illumination is required.

High quality LM80-tested LEDs

for consistent long-life performance and color

Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

SPECIFICATIONS

DELIVERED LUMENS	625.2		
WATTS	10.2		
VOLTAGE	Universal 120-277V, with integral transient 2.5kV surge protection (driver)		
DIMMING	0-10		
LIGHT DISTRIBUTION	Symmetric		
MOUNTING OPTIONS	Wall		
PERFORMANCE OPTIONS	Photocontrol / In-Line Fuse / Surge Protector		
ССТ	3000K or 4000K		
CRI	80+		
COLOR BINNING	3 Step		
BUG RATING	B1-U1-G0		
DARK SKY	Compliant		
WET LISTED	IP65		
GENERAL LISTING	ETL		
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.		
START TEMP	-30°C		
FIELD SERVICEABLE LED	Yes		
CONSTRUCTION	Aluminum		
HARDWARE	Stainless Steel		
FINISH	Powder Coat		
LED LIFETIME	L70; 70,000 Hours		
WARRANTY*	5 Years		
WEIGHT	2.5 lbs.		






TAAG 6 ze shown in charcoal

ORDERING INFORMATION

7000WTAG	CRI/CCT	LENGTH	LENS	FINISH	VOLTAGE	DISTRIBUTION	OPTIONS
	830 80 CRI, 3000K 840 80 CRI, 4000K	6 6"	D DIFFUSE	Z BRONZE H CHARCOAL	UNV 120V–277V	S Symmetric	PC BUTTON PHOTOCONTROL LF IN-LINE FUSE SP SURGE PROTECTION PCLF BUTTON PHOTOCONTROL & IN-LINE FUSE PCSP BUTTON PHOTOCONTROL & SURGE PROTECTION LFSP IN-LINE FUSE & SURGE PROTECTION BUTTON PHOTOCONTROL, IN-LINE FUSE & SURGE PROTECTION PCLFSP BUTTON PHOTOCONTROL, IN-LINE FUSE & SURGE PROTECTION

^{*} Visit techlighting.com for specific warranty limitations and details.




Taag 6

PHOTOMETRICS*

 $\hbox{``For latest photometrics, please visit www. techlighting.com/OUTDOOR'}$

TAAG 6

Total Lumen Output: 625.2
Total Power: 10.2
Luminaire Efficacy: 61
Color Temp: 4000K
CRI: 80+
BUG Rating: B1-U1-G0



PROJECT INFO

