Alumilux Prime | E41307-SA

PRODUCT DESCRIPTION

16"

12.5"
*HCO

4.25"   3.5"

*height from center of outlet to the top of the fixture

MEASUREMENTS
DIMENSION : 4.25'' W x 16'' H x 3.5'' Ext
MAX OAH :
HANGING WEIGHT : 2.79 lb

LAMPING
INPUT VOLTAGE : 120V
LUMENS : 432 Rated (259 Del.)
BULB : 5 x 1W LED PCB Integrated , 5W Total
BULB INCLUDED : (Integrated)
DIMMABLE : ELV Or Triac CL
CRI : 90+ CRI
COLOR_TEMP : 3000K
LIGHTING_DIRECTION : Indirect

FINISHES OPTION
- Black
- Satin Aluminum
- White

MATERIAL
Aluminum

RATINGS
cETLus
Wet Location
For Outdoor
ADA

ADDITIONAL
INSTALL UP/DOWN: Up
RATED LIFE 50000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.

Contemporary Lighting™

WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 I F. 626.956.4225 I et2online.com