

WAC LIGHTING

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

BLO

Ceiling and Wall Mount

Model & Size	Color Temp & CRI	Lumens	Finish
FM-113	2700K/3000K/3500K /4000K/5000K 90	1600	WT White
FM-115		2230	

Example: **FM-113-CS-WT**

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Driver included
- 5 year warranty

SPECIFICATIONS

Construction:	Aluminum with white acrylic diffuser
Power:	20W, 27W
Input:	120 -277 VAC, 50/60Hz
Dimming:	TRIAC: 100-5%, ELV: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50000 Hours
Mounting:	Installs over a 3" or 4" Junction Box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically powder coated White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed, Energy Star 2.0, Title 24 JA8-2016 Compliant, ADA, IC, Airtight



FINISHES



White

LINE DRAWING

