

ASSEMBLY INSTRUCTIONS FOR YOUR CRISTALLO CHANDELIER

SAFETY INSTRUCTIONS:

- *These instructions are provided for your safety. It is important that they are read completely before beginning installation.
- *WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.
- *Always turn off power at switch before replacing bulbs.
- *This fixture is UL rated for dry locations.
- *DUE TO THE WEIGHT OF THIS ITEM, YOUR CEILING OUTLET BOX MUST BE RATED FOR FIXTURES UP TO 150 LBS. FOLLOW MANUFACTURERS NSTRUCTIONS FOR CEILING OUTLET BOX INSTALLATION.

ASSEMBLY INSTRUCTIONS:

- 1. SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/ CIRCUIT BREAKER.
- 2. Remove all parts carefully from the carton. Do not throw away any parts.
- 3. Remove quick link (G) from hang straight (F). Keep quick link (G) attached to chain (H).
- 4. Remove cross bar (A) (with threaded tube (C) and hang straight (F) attached) from canopy (D). Do this by unthreading collar (E) from hang straight (F). Canopy (D) will slip over hang straight (F). Set the canopy (D) and collar (E) aside.
- 5. Affix cross bar (A) (with threaded tube (C) and hang straight (F) attached) to ceiling outlet box using screws (B) provided.
- 8. Measure desired drop for fixture to hang. If necessary, remove links from chain (H) with chain break tool (not included) to achieve the desired drop.
- 6. Attach quick link (I) to loop (J).
- 7. Slip collar (E) over chain (H) so it rests on loop (J). Slip canopy (D) over chain (H) so it also rests on loop (J).
- 8. Lift fixture to ceiling and secure quick link (G) to hang straight (F). Guide the wire exiting the fixture through the center of collar (E) and canopy (D). Continue to guide the wire through chain (H), quick link (G) and through the center of hang straight (F) and threaded tube (C).
- 9. Make proper electrical connections described in steps 10 12. A LICENSED ELECTRICIAN IS RECOMMENDED.
- 10. Attach ground wire from fixture (green or silver in color) to ground wire from outlet box. Fasten wires together with wire nut (O) and tightly wrap connection with electrical tape.
- 11. Attach hot wire from fixture (black in color or smooth side of wire) to hot wire from outlet box. Fasten wires together with wire nut (O) and tightly wrap connection with electrical tape.
- 12. Attach neutral wire from fixture (white in color or ribbed side of wire) to neutral wire from outlet box. Fasten wires together with wire nut (O) and tightly wrap connection with electrical tape.
- 13. Carefully push wire connections back into ceiling outlet box.
- 14. Slide canopy (D) up chain (H) and hold flush against ceiling. To secure position of canopy (D), slide collar (E) up the chain and thread it onto hang straight (F). Turn until hand tight.
- 15. Slide shade (M) over socket (N). Repeat for remaining shades.
- 16. Install (8) 60W MAX. Type B, candelabra base bulbs into sockets (N).
- 17. Reconnect main electrical supply at the fuse box/circuit breaker and test fixture.



ASSEMBLY INSTRUCTIONS FOR YOUR CRISTALLO CHANDELIER

