

Project:

Purolinear 360 LED Wall Bar Spec Sheet

SKU: 23QSWN222R120PHA Learn more at: https://sonnemanlight.com/purolinear-360-led-wall-bar

Description: A system of linear tubes, set within the geometry of surface-mounted cylinder brackets, rotate individually to direct the LED illumination in 360 degrees along their axis. Arranged in a linear pattern or along a single path, the possibilities for compositions are endless and unlimited in scalability. Set on a wall, in line behind a bed, the rotatable luminaires provide the variability of direct or indirect illumination.

Type #:



 Height:
 24.75"

 Width:
 49.25"

 Extends:
 2.75"

 Minimum Extension:
 2.75"

 Maximum Extension:
 2.75"

 Shape:
 Double N

 Size:
 24"

Electrical Specs

Bulb(s) Included?: Yes Bulb 1 Type: Integral LED Bulb Quantity: 100-277VAC Input Voltage: Wattage: Initial Lumens: 2760 **Delivered Lumens:** 1960 Color Temperature: 3000K CRI: 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: Remote Dimming Type: TRIAC/ELV/ 0-10V Bulb Max Wattage:

Installation

Installation: Licensed electrician required

Shade

Shade 1 Material: Optical Acrylic

Available Finishes

Available Finishes: Polished Chrome (.01), Satin Black (.25), Satin Chrome (.23), Satin White (.03)

General Listings

Features: ADA

Certification: Color/Finish:

Dark Sky Friendly:

ADA Compliant, Damp Rated C-ETL-US Satin White (.03) N