The Turbo outdoor LED path light features a clean, cylindrical silhouette highlighted with decorative fins evenly spaced around the circumference which create beautiful geometric shadows when illuminated by the powerful LED light source shining down from the crown.

### High quality LM80-tested LEDs

for consistent long-life performance and color

### Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

### Bolt or Stake mounting options

## **SPECIFICATIONS**

| DELIVERED LUMENS      | 1009  |
|-----------------------|---|
| WATTS                 | 16.3  |
| VOLTAGE               | 12V (Transformer sold separately)   |
| DIMMING               | MLV   |
| LIGHT DISTRIBUTION    | Symmetric   |
| MOUNTING OPTIONS      | Bolt or Stake   |
| ССТ                   | 2700К, 3000К  |
| CRI                   | 80  |
| COLOR BINNING         | 3 Step  |
| BUG RATING            | B1-U0-G0  |
| DARK SKY              | Compliant   |
| WET LISTED            | IP65  |
| GENERAL LISTING       | ETL   |
| CALIFORNIA TITLE 24   | Can be used to comply with CEC 2016 Title 24<br>Part 6 for outdoor use. Registration with CEC<br>Appliance Database not required. |
| START TEMP            | -30°C   |
| FIELD SERVICEABLE LED | Yes   |
| CONSTRUCTION          | Aluminum  |
| HARDWARE              | Stainless Steel   |
| FINISH                | Powder Coat   |
| LED LIFETIME          | L70; 70,000 Hours   |
| WARRANTY*             | 5 Years   |
| WEIGHT                | 10.5 lbs.   |

\* Visit techlighting.com for specific warranty limitations and details.



TURBO PATH shown in bronze



TURBO PATH shown in charcoal


### 12V AC TRANSFORMERS\* (OUTDOOR RATED, ORDERED SEPARATELY)

| ITEM      | DESCRIPTION          | HOUSING         | DIMMING  |
|-----------|----------------------|-----------------|----------|
| 700OT150T | MAGNETIC, 150W, 120V | STAINLESS STEEL | MAGNETIC |
| 700OT300T | MAGNETIC, 300W, 120V | STAINLESS STEEL | MAGNETIC |

# ORDERING INFORMATION

| 700OATUR          | CRI/CCT   | LENGTH        | LENS      | FINISH  | VOLTAGE       | DISTRIBUTION | OPTIONS                              |
|-------------------|---|---------------|-----------|---|---------------|--------------|--------------------------------------|
|                   | <ul><li>827 80 CRI, 2700K</li><li>830 80 CRI, 3000K</li></ul> | <b>12</b> 12" | D DIFFUSE | <ul> <li>B BLACK</li> <li>Z BRONZE</li> <li>H CHARCOAL</li> </ul> | <b>12</b> 12V | S SYMMETRIC  | CONCRETE MOUNT<br>STAKE MOUNTING KIT |
| *REQUIRES 12V REP | MOTE TRANSFORMER  |               |           |   |               |              |                                      |


# TURBO PATHWAY



# PHOTOMETRICS\*

### TURBO PATH 20°

| Total Lumen Output: | 1009     |
|---------------------|----------|
| Total Power:        | 16.3     |
| Luminaire Efficacy: | 64.4     |
| Color Temp:         | 3000K    |
| CRI:                | 80+      |
| BUG Rating:         | B1-U0-G0 |



# PROJECT INFO

### FIXTURE TYPE & QUANTITY

(II)

JOB NAME & INFO

 $\otimes$  2020 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark. Tech Lighting reserves the right to change specifications for product improvements without notification.

NOTES

# TECH LIGHTING

# VISUAL COMFORT & CO.

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

\*For latest photometrics, please visit www. techlighting.com/OUTDOOR