The Aspenti wall sconce adds the perfect finish to any exterior space. With its cylindrical profile and modern industrial appearance, the Aspenti features up and down light for optimal illumination making it ideal for a number of commercial or residential outdoor lighting applications.

Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

SPECIFICATIONS

DELIVERED LUMENS	1028.4
WATTS	14
VOLTAGE	120V, 277V
DIMMING	ELV
LIGHT DISTRIBUTION	Symmetric
OPTICS	36°
MOUNTING OPTIONS	Wall
ССТ	3000K
CRI	90
COLOR BINNING	3-Step
BUG RATING	B1-U3-G0
DARK SKY	Non-compliant
WET LISTED	IP65
GENERAL LISTING	ETL
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	Yes
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Powder Coat
LED LIFETIME	L70; 70,000 hours
WARRANTY*	
νναππαινιτ	5 years
WEIGHT	5 years 8 lbs.



ASPENTI 20 shown in bronze




ASPENTI 20 shown in charcoal

* Visit techlighting.com for specific warranty limitations and details.

ORDERING INFORMATION

7000WAST	SIZE	FINISH	LAMP	
	20 20"	Z BRONZE H CHARCOAL	LED930 LED930277	LED 90CRI, 3000K, 120V LED 90CRI, 3000K, 277V




Aspenti 20

PHOTOMETRICS*

ASPENTI 20

Total Lumen Output:	1028.4
Total Power:	13.7
Luminaire Efficacy:	75
Color Temp:	3000K
CRI:	90
BUG Rating:	B1-U3-G0



PROJECT INFO

FIXTURE TYPE & QUANTITY

(I)

JOB NAME & INFO

 \odot 2020 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark. Tech Lighting reserves the right to change specifications for product improvements without notification.

NOTES

TECH LIGHTING

VISUAL COMFORT & CO.

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

*For latest photometrics, please visit www. techlighting.com/OUTDOOR