

# WAC LIGHTING

## VENTRIX

### Multi Stealth Downlights

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

Model & size	Power	Watt	Beam	Color Temp & CRI	Delivered Lumens	CBCP	Finish	
S2MD06	1	3.5W	F 45°	927 2700K - 90	260	430	BK Black	
	1	3.5W	F 45°	930 3000K - 90	270	450	CH Chrome	
	1	3.5W	F 45°	935 3500K - 90	280	470	GL Gold	
	1	3.5W	F 45°	940 4000K - 90	290	480	HZ Haze	
	1	3.5W	N 32°	927 2700K - 90	260	610	WT White	
	1	3.5W	N 32°	930 3000K - 90	270	640		
	1	3.5W	N 32°	935 3500K - 90	280	670		
	1	3.5W	N 32°	940 4000K - 90	290	680		
	1	3.5W	S 16°	927 2700K - 90	250	1230		
	1	3.5W	S 16°	930 3000K - 90	260	1290		
	1	3.5W	S 16°	935 3500K - 90	270	1350		
	1	3.5W	S 16°	940 4000K - 90	280	1380		
	2	5W	F 45°	927 2700K - 90	400	640		
	2	5W	F 45°	930 3000K - 90	420	670		
	2	5W	F 45°	935 3500K - 90	440	700		
	2	5W	F 45°	940 4000K - 90	450	720		
	2	5W	N 32°	927 2700K - 90	390	950		
	2	5W	N 32°	930 3000K - 90	410	1000		
	2	5W	N 32°	935 3500K - 90	430	1050		
	2	5W	N 32°	940 4000K - 90	440	1070		
	2	5W	S 16°	927 2700K - 90	380	1820		
	2	5W	S 16°	930 3000K - 90	400	1920		
	2	5W	S 16°	935 3500K - 90	420	2020		
	2	5W	S 16°	940 4000K - 90	430	2050		
	3	6W	F 45°	927 2700K - 90	490	860		
	3	6W	F 45°	930 3000K - 90	520	910		
	3	6W	F 45°	935 3500K - 90	550	960		
	3	6W	F 45°	940 4000K - 90	560	970		
	3	6W	N 32°	927 2700K - 90	480	1290		
	3	6W	N 32°	930 3000K - 90	510	1360		
	3	6W	N 32°	935 3500K - 90	540	1430		
	3	6W	N 32°	940 4000K - 90	550	1460		
	3	6W	S 16°	927 2700K - 90	450	2570		
	3	6W	S 16°	930 3000K - 90	470	2710		
	3	6W	S 16°	935 3500K - 90	490	2850		
	3	6W	S 16°	940 4000K - 90	500	2900		
	S2MD12	1	5.5W	F 45°	927 2700K - 90	480	900	
		1	5.5W	F 45°	930 3000K - 90	510	950	
		1	5.5W	F 45°	935 3500K - 90	540	1000	
		1	5.5W	F 45°	940 4000K - 90	550	1020	
1		5.5W	N 32°	927 2700K - 90	480	1320		
1		5.5W	N 32°	930 3000K - 90	510	1390		
1		5.5W	N 32°	935 3500K - 90	540	1460		
1		5.5W	N 32°	940 4000K - 90	550	1490		
1		5.5W	S 16°	927 2700K - 90	490	2460		
1		5.5W	S 16°	930 3000K - 90	520	2590		
1		5.5W	S 16°	935 3500K - 90	550	2720		
1		5.5W	S 16°	940 4000K - 90	560	2770		
2		8W	F 45°	927 2700K - 90	710	1350		
2		8W	F 45°	930 3000K - 90	750	1420		
2		8W	F 45°	935 3500K - 90	790	1490		
2		8W	F 45°	940 4000K - 90	800	1520		
2		8W	N 32°	927 2700K - 90	720	1960		
2		8W	N 32°	930 3000K - 90	760	2060		
2		8W	N 32°	935 3500K - 90	800	2160		
2		8W	N 32°	940 4000K - 90	810	2200		
2		8W	S 16°	927 2700K - 90	730	3790		
2		8W	S 16°	930 3000K - 90	770	3990		
2		8W	S 16°	935 3500K - 90	810	4190		
2		8W	S 16°	940 4000K - 90	820	4270		
3		10.5W	F 45°	927 2700K - 90	940	1770		
3		10.5W	F 45°	930 3000K - 90	990	1860		
3		10.5W	F 45°	935 3500K - 90	1040	1950		
3		10.5W	F 45°	940 4000K - 90	1060	1990		
3		10.5W	N 32°	927 2700K - 90	950	2570		
3		10.5W	N 32°	930 3000K - 90	1000	2710		
3		10.5W	N 32°	935 3500K - 90	1050	2850		
3		10.5W	N 32°	940 4000K - 90	1070	2900		
3		10.5W	S 16°	927 2700K - 90	960	4870		
3		10.5W	S 16°	930 3000K - 90	1010	5130		
3		10.5W	S 16°	935 3500K - 90	1060	5390		
3		10.5W	S 16°	940 4000K - 90	1080	5490		
S2MD24		1	10W	F 45°	927 2700K - 90	950	1610	
		1	10W	F 45°	930 3000K - 90	1000	1690	
		1	10W	F 45°	935 3500K - 90	1050	1770	
		1	10W	F 45°	940 4000K - 90	1070	1810	
	1	10W	N 32°	927 2700K - 90	950	2270		
	1	10W	N 32°	930 3000K - 90	1000	2390		

wacighting.com | Phone (800) 526.2588 | Fax (800) 526.2589 | Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. May 2024

# WAC LIGHTING

1	10W	S 16°	927 2700K - 90	960	4810
1	10W	S 16°	930 3000K - 90	1010	5060
1	10W	S 16°	935 3500K - 90	1060	5310
1	10W	S 16°	940 4000K - 90	1080	5410
2	15.5W	F 45°	927 2700K - 90	1480	2510
2	15.5W	F 45°	930 3000K - 90	1560	2640
2	15.5W	F 45°	935 3500K - 90	1640	2770
2	15.5W	F 45°	940 4000K - 90	1670	2820
2	15.5W	N 32°	927 2700K - 90	1480	3520
2	15.5W	N 32°	930 3000K - 90	1560	3700
2	15.5W	N 32°	935 3500K - 90	1640	3890
2	15.5W	N 32°	940 4000K - 90	1670	3960
2	15.5W	S 16°	927 2700K - 90	1470	6600
2	15.5W	S 16°	930 3000K - 90	1550	6950
2	15.5W	S 16°	935 3500K - 90	1630	7300
2	15.5W	S 16°	940 4000K - 90	1660	7440
3	21.5W	F 45°	927 2700K - 90	1920	3420
3	21.5W	F 45°	930 3000K - 90	2020	3600
3	21.5W	F 45°	935 3500K - 90	2120	3780
3	21.5W	F 45°	940 4000K - 90	2160	3850
3	21.5W	N 32°	927 2700K - 90	1950	5000
3	21.5W	N 32°	930 3000K - 90	2050	5260
3	21.5W	N 32°	935 3500K - 90	2150	5520
3	21.5W	N 32°	940 4000K - 90	2190	5630
3	21.5W	S 16°	927 2700K - 90	1840	8830
3	21.5W	S 16°	930 3000K - 90	1940	9290
3	21.5W	S 16°	935 3500K - 90	2040	9750
3	21.5W	S 16°	940 4000K - 90	2080	9940

Example: **S2MD06-1-F927BK**

## DESCRIPTION

Multi Stealth Downlights feature a quiet aperture for a nearly glare free environment. With multiple lumen packages, beam and finish options, these downlights complement other elements in your VENTRIX array. Three output selections provide up to 1120 lumens per foot.

## FEATURES

- Three power levels for precision output
- Low glare multi-cell trim with 40° cutoff angle
- Interchangeable trim available in 5 finishes
- May be installed side by side for seamless appearance
- To enable access to VENTRIX element releasing tabs, maintain at least 3" of free channel space
- Driver concealed within the fixture
- 5 year warranty

## SPECIFICATIONS

Construction:	Extruded aluminum with injection molded low glare trim
Power:	3.5W, 5.5W, 5W, 6W, 8W, 10.5W, 10W, 15.5W, 21.5W
Input:	48 VDC
Dimming:	ELV: 100-0.1% , 0-10V: 100-0.1%, TRIAC: 100-0.1%
Light Source:	Integrated LED 3 Step Mac Adam Ellipse
Rated Life:	50000 Hours
Mounting:	Installs magnetically and mechanically into VENTRIX system, Can be mounted on ceiling or wall vertically or horizontally
Finish:	Injection Molded Polycarbonate: Gold, Haze, Black, Chrome, White, Injection Molded Polycarbonate: Haze, Gold, Injection Molded Polycarbonate: Black
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed, Title 24 JA8 Compliant



## FINISHES:



## LINE DRAWING:

## REPLACEMENT PARTS

REF-S2MD06-BK - Multi Stealth Downlight Trim

REF-S2MD06-CH - Multi Stealth Downlight Trim

WAC Lighting.com | Phone (800) 526.2588 | Fax (800) 526.2585 | Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. May 2024


# WAC LIGHTING

REF-S2MD06-GL - Multi Stealth Downlight Trim


REF-S2MD06-HZ - Multi Stealth Downlight Trim

REF-S2MD06-WT - Multi Stealth Downlight Trim

S2MD06



S2MD12



S2MD24

