MT-3LD111 - 1 Light

Mini LED Multiple Spots



Responsible Lighting®

W	1			
W)/		
	and a second			



Fixture Type:	
Catalog Number:	
Project:	

Location:

PRODUCT DESCRIPTION

Integral housing adjustable recessed spot light.

FEATURES

- Individually adjustable luminaires
- Complete unit includes housing & trim
- All housings are Non-IC rated
- 30° visual cutoff for glare control
- 25° vertical tilt. 350° horizontal rotation.

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box (New Construction): Seven knockouts and four Romex[®] style wiring connectors provided for ease of installation. Rated for branch wiring.

Г

Driver: 120VAC Input

Light Source: High output LED (included with housing)

Dimming: Dim to 10% with electronic low voltage (ELV) dimmer.

Mounting: Supplied with hanger bars, adjustable from 14½"-25" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 4¼" × 4¼" cutout.

Finish: Abrasion resistant powder coat paint in Black (BK).

Standards: ETL & cETL Damp Location listed; Energy Star rated

			Power Bear		Beam Color Temp		CRI	Lumens	CBCP	Finish		
				F	25°	927 930	2700K 3000K	90 90	710 785	1886 2176	ВК	White trim with black interior
+15" →9%" 5%" 5%"	85%" 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	MT-3LD1111NA New Construction Non-IC, Airtight	11W	F	• 25*	935 940	3500K 4000K	90 90	795 805	2184 2224	wт	White trim with white interior
					_	927 930	2700K 3000K	90 90	705 775	911 1015	BK	White trim wit black interior
				w	45°	935 940	3500K 4000K	90 90	785 795	1024 1042	wт	White trim with white interior
	$\begin{bmatrix} \begin{bmatrix} \bullet \\ - \end{bmatrix} \end{bmatrix}_{i=1}^{a} 4^{\frac{1}{2}}_{4}^{u}$ $- 4^{\frac{1}{2}}_{4}^{u}$	MT-3LD111R Remodel Non-IC	11W		0.50	927 930	2700K 3000K	90 90	710 785	1886 2176	вк	White trim wit black interior
				F	25°	935 940	3500K 4000K	90 90	795 805	2184 2224	wт	White trim wit white interior
					450	927 930	2700K 3000K	90 90	705 775	911 1015	вк	White trim wit black interior
				w	45°	935 940	3500K 4000K	90 90	785 795	1024 1042	wт	White trim wi white interior

Example: MT-3LD111R-F30-BK

WAC Lighting

www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JAN 2018