

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Stretch LED Swing Arm

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
BL-1630 1 Light	3000K 90	7.5W	489	260	BK Black
BL-1660 2 Light		17.2W	936	623	TT Titanium WT White

Example: **BL-1630-BK**

DESCRIPTION

A contemporary utilitarian design. Stretch incorporates a rubberized flexible and fixable arm as part of this unique modern design. The die-cast aluminum head also serves as the heat sink for the powerful 7.5 watt LED.

FEATURES


- A contemporary utilitarian design
- Flexible rubber tube for aiming
- Two 12" cord covers included
- Fingertip touch dimming on head
- Integral driver
- 8 foot cord included for hard-wired and portable installation
- Conversion plate for 4" junction box included
- Hold switch to dim
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS

Construction:	Steel canopy, flexible tubing with die-cast aluminum head with etched glass diffuser
Power:	17.2W, 7.5W
Input:	100-240 VAC, 50/60Hz
Rated Life:	30000 Hours
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard.
Finish:	White, Black, Titanium
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed



FINISHES



LINE DRAWING

