

NLOPAC-R4T24

4" AC T24 Opal - LED Surface Mount

Source: 13W LED
850lm

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

The AC Opal LED Series LED fixture is designed to surface mount over a standard junction box. The low profile dimmable luminaire produces even illumination and is cULus listed for wet locations.

FEATURES

- AC LED (No Driver)
- Dimmable
- Mount on standard 4" junction box
- ENERGY STAR certified

SPECIFICATION

Construction: One piece aluminum die formed housing and trim. Aluminum body dissipates heat and extends life.

Mounting: AC Opal (no driver) is flat on the back and suitable for installation on most 4" octagon boxes or 4/0 plaster ring. Luminaires can be installed in covered ceiling and wall mount.

Optics: Nora specified and designed precision molded lens for optimal lumen output and even distribution.

Ratings: IC rated when used with a 4" electrical junction box rated for direct contact with insulation. Fire rated when used with a fire rated junction box.

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage: 850lm / 13W

Color Temperature: 2700K or 4000K (3000K discontinued, see: [NLOPAC-R4509T24](#))

Color Rendering Index: 90+ CRI

Operating Temperature: 0-45°C

Dimming: 5% with Triac or 10% with ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

ACCESSORIES


NLOPAC-4BKT-2: Universal bracket for mounting to 3" or 4" junction boxes.

LISTING

- cULus Listed for wet locations (covered ceiling only)
- ENERGY STAR certified
- [5-Year Limited Warranty](#)
- RoHS Compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2019
- Suitable for use in closets when installed in accordance to NEC Section 410.16 (A)(1) and 410.16 (C)(1).



PRODUCT IMAGES AND DIMENSIONS



BZ
Bronze



W
White



NLOPAC-4BKT-2
Universal Bracket for 3" or 4" Junction Boxes

4" AC T24 Opal - LED Surface Mount

Color Temperature / Finish

- NLOPAC-R4T2427BZ** = 2700K / Bronze
- NLOPAC-R4T2427NM** = 2700K / Natural Metal (Discontinued, direct replacement: [NLOPAC-R4509T2427NM](#))
- NLOPAC-R4T2427W** = 2700K / White (Discontinued, direct replacement: [NLOPAC-R4509T2427W](#))
- NLOPAC-R4T2430BZ** = 3000K / Bronze (Discontinued, direct replacement: [NLOPAC-R4509T2430BZ](#))
- NLOPAC-R4T2430NM** = 3000K / Natural Metal (Discontinued, direct replacement: [NLOPAC-R4509T2430NM](#))
- NLOPAC-R4T2430W** = 3000K / White (Discontinued, direct replacement: [NLOPAC-R4509T2430W](#))
- NLOPAC-R4T2440BZ** = 4000K / Bronze
- NLOPAC-R4T2440NM** = 4000K / Natural Metal (Discontinued, direct replacement: [NLOPAC-R4509T2440NM](#))
- NLOPAC-R4T2440W** = 4000K / White

Optional Accessories

Description

NLOPAC-4BKT-2 = Universal Bracket for 3" or 4" Junction Boxes

Example: **NLOPAC-R4T2440W** = 4" AC T24 Opal, 850lm / 13W, 4000K, White finish