

BASICS

120V/24VDC 60W Electronics Transformer

Model	Finish		
EN-BT60-24			
EN-BT96-24			
Example: EN-BT60-24			

FEATURES

- Input: 120 VAC, 50/60Hz
- 6" Output lead wires
- ELV Dimming (100-10%)
- Secondary wiring for Class 2 transformers does not require conduit sheathed cable or clamp wiring techniques
- \bullet Intrinsically safe, Class 2 transformers permit no greater than a 5 amp current be drawn
- Non-metallic sheathed cable may be used for secondary wiring in walls and ceilings
- Built-in auto reset, soft start, short and overload circuit
- 5 Year warranty

SPECIFICATIONS

Input: 120 VAC, 50/60Hz
Dimming: ELV: 100-10%
Rated Life: 50000 Hours

Mounting: Mounting metal case with screws, Can be

mounted on ceiling or wall in all orientations

Operating Temp: $-4^{\circ}F$ to $104^{\circ}F$ ($-20^{\circ}C$ to $40^{\circ}C$)

Standards: UL, cUL, Damp Location Listed, IP20, ADA

Fixture Type:

Catalog Number:

Project:

Location:





BASICS

1	201	//24\/ Γ	C 60W	Flectr	onics '	Transform	ρΙ
1	ZU V	// ᠘ 4 ۷	\sim 00 $^{\circ}$	LIECU	ULIICS	11 al 13101111	CI

Fixture Type:	
Catalog Number:	
Project:	
Location:	

ACCESSORIES	
-------------	--

	Model	Description	Finish
or or po	LED-T-B	InvisiLED®	White
\$	T24-BS-MM-CL	BASICS	CLEAR
S. ET	T24-BS-PM-CL	BASICS	CLEAR
	T24-BS-X-WT	BASICS	WHITE
	T24-BS-Y-WT	BASICS	WHITE
•	T24-BS-EX2-072-WT	BASICS	WHITE
	T24-BS-IC-002-WT	BASICS	WHITE