VOTO 8 WALL SCONCE

TECH LIGHTING

In dramatic contrast to the die-cast metal body, two symmetrical reveals cut from a solid piece of optically pure acrylic adorn the top and bottom of the Voto wall sconce. Beautiful LED light pours from the top and bottom of the thick-cut acrylic to provide ample illumination. Also available as a downlight or uplight to meet the needs of all outdoor applications.

High quality LM80-tested LEDs

for consistent long-life performance and color

Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

Up light and down light option

SPECIFICATIONS

DELIVERED LUMENS	1394 Up-Downlight / 672.5 Downlight
WATTS	27.8 Up-Downlight / 14.2 Downlight
VOLTAGE	Universal 120-277V, with integral transient 2.5kV surge protection (driver)
DIMMING	0-10, ELV
LIGHT DISTRIBUTION	Symmetric Up/Down Lighting, or Down Only
MOUNTING OPTIONS	Wall
PERFORMANCE OPTIONS	Surge Protector
ССТ	3000K or 4000K
CRI	80+
COLOR BINNING	3 Step
BUG RATING	Up-Downlight B0-U4-G1 / Downlight B0-U2-G1
DARK SKY	Compliant (Downlight)
WET LISTED	IP65
GENERAL LISTING	ETL
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	Yes
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Powder Coat
LED LIFETIME	L70; 70,000 Hours
WARRANTY*	5 Years
WEIGHT	9.6 lbs.



VOTO 8, DOWN ONLY shown in bronze



VOTO 8, UP/DOWN shown in bronze



VOTO 8, DOWN ONLY shown in charcoal



VOTO 8, UP/DOWN shown in charcoal


* Visit techlighting.com for specific warranty limitations and details.

ORDERING INFORMATION

700OWVOT	CRI/CCT	LENGTH	FINISH	FUNCTION*	VOLTAGE	DISTRIBUTION	OPTIONS
	827 80 CRI, 2700K 830 80 CRI, 3000K 840 80 CRI, 4000K	8 8"	Z BRONZEH CHARCOAL	DO DOWNLIGHT ONLY UD UPLIGHT /DOWNLIGHT	UNV 120V–277V	S SYMMETRIC	NONE SP SURGE PROTECTION
*DOWNLIGHT - 9W/850 LUMENS: UP & DOWNLIGHT - 18W/1500 LUMENS							

VOTO 8 WALL SCONCE

TECH LIGHTING




Voto Large, Down Only

Voto Large, Up/Down

PHOTOMETRICS*


VOTO 8 UP/DOWN

Total Lumen Output:	1394
Total Power:	27.8
Luminaire Efficacy:	50
Color Temp:	4000K
CRI:	80+
BUG Rating:	B0-U4-G1



VOTO 8 DOWN

Total Lumen Output:	672.5
Total Power:	14.2
Luminaire Efficacy:	47
Color Temp:	3000K
CRI:	80+
BUG Rating:	B0-U2-G1



PROJECT INFO

FIXTURE TYPE & QUANTITY

JOB NAME & INFO

NOTES

TECH LIGHTING

VISUAL COMFORT & CO. 7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

© 2020 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark. Tech Lighting reserves the right to change specifications for product improvements without notification.

techlighting.com

*For latest photometrics, please visit www. techlighting.com/OUTDOOR