


# Revolve Duo

Our Recessed family has grown with a new range of adjustable downlights. The effortless design and high functionality of these fixtures are sure to make a welcome addition in any room.

**NEW** WET SWIVEL/DIRECTIONAL 90° ETL IC RATED

AIR TIGHT 2700k 3000k 3500k 4000k 5000k ENERGY STAR JA8 CERTIFIED



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>GBR35-CC-DUO</b>	4"	24 W	1740 lm	1815 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V

### Specifications

Includes a junction box with integrated dimmable driver  
 Can be daisy chained  
 Superior LED performance and lifespan  
 90° tilting, 360° rotation  
 Minimal heat emission  
 Aluminum construction  
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K  
 Low profile  
 40° beam spread  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 Suitable for wet locations  
 Ideal operating temperature: -20° to 40° C  
 5-year warranty

### Finish

○ **WH** White

### Accessories

**RFP-DUO**  
 Rough-in plate

### Note

Other color °T, finishes, and voltage options are available but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

**GBR35-CC-DUO** 7-1/8" x 3-1/2" 