

# SONGBIRD Wall Sconce

120v : **3-589-xxx**

277v : **37-589-xxx**

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-14 Polished Chrome



-24 Satin Nickel



-1 White Opal Glass



-2 Matte White Acrylic



-6 Silver Cloth Acrylic

**LIGHT SOURCE** 1 x 10.1W LED, 3000K, CRI 90

**LUMINAIRE POWER** 13.3W at 120V

**RATED LIFE** 60000 hr RL

**OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K

**LUMEN OUTPUT** Delivered: (-1) Glass: 1007 lm (LM-79)  
 (-2) Acrylic: 983 lm (LM-79)  
 (-6) Acrylic: 553 lm (LM-79)



**INPUT VOLTAGE** 120V or 277V

**DRIVER OUTPUT** 350mA, 12W

**DIMMING** 0-10v & Phase (ELV) Dimming - 50/60Hz 100% to 10% Dimming

**CONSTRUCTION** Plated Steel and Acrylic

**DIFFUSER / METAL FINISHES**  
 (-114) White Opal Glass / Polished Chrome  
 (-124) White Opal Glass / Satin Nickel  
 (-214) Matte White Acrylic / Polished Chrome  
 (-224) Matte White Acrylic / Satin Nickel  
 (-614) Silver Cloth Acrylic / Polished Chrome  
 (-624) Silver Cloth Acrylic / Satin Nickel



**DIMENSIONS**

**W:** 5.88"  
**H:** 17.00"  
**Ext:** 4.00"  
**M.C:** 6.50" From top of fixture

**MOUNTING** 4" Octagonal J-Box

**STANDARDS** ETL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.

Order example for standard fixture:

**3-589-624** (x- Voltage - xxx-Sequence # - x-Diffuser - xx-Finish)

**3:** 120v, **37:** 277v

Order example for optional color temperatures: **3-589-27624**

**27:** 2700K, **35:** 3500K, **40:** 4000K

