

# NATL-5030HW / NATL-5100HW

24V Class II Non-Dimmable Hardwire LED Driver

Source: 100-240V Input / 24V Output

30W or 81.6W

Type

Project

Catalog No.

Notes

## PRODUCT DESCRIPTION

24V enclosed driver to be used with Nora Lighting's 24 Volt systems.

## FEATURES

- Non-dimmable
- Conduit access wiring compartment
- Meet Class II output limits
- 24V DC rated output
- Includes 10' power line connector (NATL-10)
- cULus listed enclosure & cULus recognized driver

## ELECTRICAL

**Input Voltage:** 100-240V

**Output Voltage:** 24VDC

**Wattage:** 30W (NATL-5030HW) or 81.6W (NATL-5100HW)

**Dimming:** Non-Dimmable

## COMPATIBLE NORA 24V SYSTEMS

LED Drivers are compatible with Nora Lighting's 24V systems

SERIES	DESCRIPTION
<a href="#">NMP2-A</a>	24V Josh Adjustable
<a href="#">NMP2-LED</a>	24V Josh Fixed
<a href="#">NUTP1</a>	24V Standard Tape Light (Silicone Encapsulated)
<a href="#">NUTP3</a>	24V RGB Color Changing Tape Light
<a href="#">NUTP5</a>	24V Hy-Brite Tape Light
<a href="#">NUTP7</a>	24V Standard Tape Light (Non-Encapsulated)
<a href="#">NUTP8</a>	24V High Output Tape Light
<a href="#">NUTP9</a>	24V Side-Lit Tape Light
<a href="#">NUTP10</a>	24V CCT Color Changing Tape Light
<a href="#">NUTP11</a>	24V RGBW Color Changing Tape Light
<a href="#">NUTP51</a>	24V Continuous Hy-Brite Tape Light
<a href="#">NUTP71</a>	24V Continuous Standard Tape Light
<a href="#">NUTP81</a>	24V Continuous High Output Tape Light
<a href="#">NULB</a>	24V Lightbar Silk SBC

## OPTIONAL ACCESSORIES

**NATL-10:** 10' Power Line Connector (included)

**NATL-30:** 30' Power Line Connector


**NATL-302W:** Power Line Splitter, white cable. Splits power line connector into two separate connections.

## LABELS AND LISTINGS

- cULus Listed
- FCC compliant



## PRODUCT IMAGES & DIMENSIONS



### NATL-5030HW / NATL-5100HW

24V Class II Non-Dimmable Hardwire LED Driver



### NATL-10 / NATL-30

Power Line Connector (10' included)



### NATL-302W

Power Line Splitter

## 24V Class II Non-Dimmable Hardwire LED Driver

Output Voltage / Wattage

**NATL-5030HW** = 24V Output / 30W

**NATL-5100HW** = 24V Output / 81.6W

## Optional Accessories

Description

**NATL-10** = 10' Power Line Connector (included w/each driver)

**NATL-30** = 30' Power Line Connector

**NATL-302W** = Power Line Splitter, White

Example: **NATL-5100HW** = 24V 81.6W Class II Non-Dimmable Hardwire LED Driver