



# GLIDE

12V MINI PENDANTS

location:  
**DRY**

## SPECIFICATIONS:

### DESCRIPTION

Low voltage mini pendant with concrete lamp cover.

### LAMPING

**Standard:** 20W Shielded flood 12V halogen MR11 lamp, lamp included.

**LED:** 3W Replaceable 12V LED MR11, dimmable, 82+ CRI, 2700°K CCT, 230 lumens, 40,000 hours. Lamp included.

### DIFFUSER

Shade shall be made of concrete in various finishes. 2" Dia. x 4" H

### CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish.

### STANDARD PENDANT

Mini pendant comes complete with flat-style canopy.

### METAL FINISH


Hardware and canopies are finished in Bronze or Satin Nickel.

### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



NATURAL (GLIDENA), WHITE (GLIDEWH) & TAN (GLIDETN) WITH BRONZE FINISH



**For ordering information, see next page**

All dimensions provided are nominal.  
Allowance must be made for dimensional tolerance in handcrafted glasses.

**REV 3/16**



# GLIDE

12V MINI PENDANTS


## ORDERING:

CONNECTION	SHADE OPTIONS	LAMP OPTIONS	METAL FINISH
Pendant Fixtures	<b>GLIDENA</b> Natural	(blank) 20W MR11 Hal	<b>BR</b> Bronze
<b>1XT</b> Flat Canopy	<b>GLIDETN</b> Tan	<b>LED</b> 3W LED	<b>SN</b> Satin Nickel
	<b>GLIDEWH</b> White		

**Ex. 1XT-GLIDEWH-SN**  
Glide Pendant, White,  
Satin Nickel Finish

## FIXED PENDANT OPTION:

### 1XT 1 Light Pendant, Flat Canopy



- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer, fits partially in junction box
- Installs to standard 4" octagonal junction box
- Bronze or Satin Nickel metal finishes

### 12V LED MR11 TYPE LAMPS:

#### 3W Replacable LED:

- 3W LED lamp
- 230 lumens
- 12V input only
- Rated life: 40,000 hours
- CRI: 82+
- CCT: 2700°K
- Dimmable

### Project Information: