



PELLA 13 / 16

FLUSH MOUNT CEILING

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Flush-mounted ceiling fixture, featuring contoured one-piece handcrafted glass diffuser.

LAMPING

LED: 16W Integrated source, 120V, dimmable, 85+ CRI, 3000°K CCT, 1600 lumens, 30,000 hours, included. (For Pella 13 only)

LED: 20W Integrated source, 120V, dimmable, 85+ CRI, 3000°K CCT, 2200 lumens, 30,000 hours, included. (For Pella 16 only)

DIFFUSER

Handcrafted glass diffuser in Opal Matte with outer surface in various decors.

Pella 13: 12.5" Dia. x 3" H

Pella 16: 15.75" Dia. x 3.25" H

CONSTRUCTION

Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.

90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



CHALK

OPAL MATTE



CHERRY



OAK



For ordering information, see next page


All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 1/17



ORDERING:


Pella 13:



FIXTURES	LAMP OPTIONS
PELLA1307C Opal Matte	LED 16W LED 120V,
PELLA13CHC Cherry	1600 lumens
PELLA130KC Oak	
PELLA13KRC Chalk	

Ex. PELLA13CHC-LED
Pella 13 LED Ceiling, Cherry

Pella 16:



FIXTURES	LAMP OPTIONS
PELLA1607C Opal Matte	LED 20W LED 120V,
PELLA16CHC Cherry	2200 lumens
PELLA160KC Oak	
PELLA16KRC Chalk	

Ex. PELLA16CHC-LED
Pella 16 LED Ceiling, Cherry

Project Information: