

Project:

## Thin-Line LED Pendant Spec Sheet

SKU: 2818.25-3 Learn more at:


https://sonnemanlight.com/thin-line-led-pendant

Description:

A system of minimally scaled LED linear pendants, uplight/downlight wall bars, and indirect light wall bars, Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Thin-Line pendants are available in single- and double-sided configurations; the single-sided configurations can be installed as a downlight or up-light, providing direct or indirect illumination. Our Optional Mini Box Canopy is also available for the Thin-Line LED Pendant.

Type #:





#### **Dimensions**

 Height:
 5"

 Width:
 36"

 Length:
 0.75"

 Canopy/Backplate/Base:
 4.5"

Size: 3' Two-Sided

Canopy/Backplate/Base Height: 0.5

### Installation

Installation:

Licensed electrician required

Sloped Ceiling Compatible?:

Minimum Hanging Height:

Maximum Hanging Height:

73.75"

## **General Listings**

Damp Rated

C-ETL-US

Satin Black

(.25)

Ň

Features: Certification: Color/Finish:

Dark Sky Friendly:

# **Electrical Specs**

Bulb(s) Included?: Yes Bulb 1 Type: Integral LED Bulb Quantity: 2 120VAC Input Voltage: Wattage: 38 Initial Lumens: 2220 **Delivered Lumens:** 1350 Color Temperature: 3000K 90 CRI: Power Supply Type: Driver Power Supply Quantity: Remote Power Supply Location: Dimming Type: TRIAC/ELV Bulb Max Wattage: 38

## **Shipping**

Carton 1 L x W x H: 40" X 7" X 4" Carton 1 Gross Weight: 6 LBS

### **Shade**

Shade 1 Material: Aluminum w/Optical

Acrylic

## **Available Finishes**

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)