
Superpuck surface



Enjoy energy saving white light in a variety of attractive finishes. These LED pucks are well suited to accent and task lighting under cabinets and in other areas.



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
4002	Ø2.625"	1.6 W	168 lm	90	3000 K	12 V
4002HP	Ø2.625"	2.9 W	298 lm	90	3000 K	12 V

Specifications

12V DC LED driver required
 Over 50,000 hours of service life
 12" input lead with quick connector
 24" interconnection harness included
 Warm white light output
 Superior LED performance and lifespan
 Smooth 360° wide spread
 Minimal heat emission
 Heat sink and thermal protection
 Steel and aluminum construction
 Frosted glass lens
 Refer to website for dimmer compatibility
 5-year warranty
 Kits available

Note

Plug-in or hard-wired power supply required for installation. Sold separately.

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

Power supplies: plug-in

- ETR-LED10WPI**
12VDC/10W class 2 LED driver
- ETR-LED24WPI**
12VDC/24W class 2 LED driver

Power supplies: hard-wired

- BT06DIM-IC**
6W dimmable LED hardwire driver
- BT12DIM-IC**
12W dimmable LED hardwire driver
- BT24DIM-IC**
24W dimmable LED hardwire driver
- BT36DIM**
36W dimmable LED hardwire driver
- BT48DIM**
48W dimmable LED hardwire driver

Accessories

- 4000E-24**
24" extension cord
- 4000E-60**
60" extension cord
- 4000HRNS-24**
24" interconnection harness

Order example

- 4002-BK**
4002 single puck with a 1.6W LED array with 168 lumens at 3000K in a black finish



4002

