

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Frame

### Pendant 3000K

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens	Title 24
PD-29828 28"	3000K 90	AL Brushed Aluminum	55W	6334	5131	Yes
	3000K 90	BK Black	55W	6334	5131	Yes

Example: **PD-29828-AL**

#### DESCRIPTION

An extruded acrylic diffuser with mitered edges gives this design a clean, elevated look, evenly spreading the powerful LED light for a geometric illumination that matches back to the rectilinear canopy.

#### FEATURES


- Thin color matched powered aircraft cables and hardware
- Crisp mitered joints
- Can be mounted on a sloped ceiling
- Driver concealed within the canopy
- 5 year warranty

#### SPECIFICATIONS


<b>Color Temp:</b>	3000K
<b>Input:</b>	120-277 VAC, 50/60Hz
<b>CRI:</b>	90
<b>Dimming:</b>	ELV: 100 - 10%, 0-10V: 100 - 3%
<b>Rated Life:</b>	50000 Hours
<b>Mounting:</b>	Heavy gauge retention clips support trim firmly. Safety cabling standard.
<b>Standards:</b>	ETL, cETL, Title 24 JA8-2016 Compliant Damp Location Listed
<b>Construction:</b>	Aluminum body with extruded acrylic diffuser



#### FINISHES



#### LINE DRAWING



Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Frame

### Pendant 3000K

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens	Title 24
PD-29858 58"	3000K 90	AL Brushed Aluminum	58W	7160	5800	Yes
	3000K 90	BK Black	58W	7160	5800	Yes

Example: **PD-29858-AL**

#### DESCRIPTION

An extruded acrylic diffuser with mitered edges gives this design a clean, elevated look, evenly spreading the powerful LED light for a geometric illumination that matches back to the rectilinear canopy.

#### FEATURES


- Thin color matched powered aircraft cables and hardware
- Crisp mitered joints
- Can be mounted on a sloped ceiling
- Driver concealed within the canopy
- 5 year warranty

#### SPECIFICATIONS

<b>Color Temp:</b>	3000K
<b>Input:</b>	120-277 VAC, 50/60Hz
<b>CRI:</b>	90
<b>Dimming:</b>	ELV: 100 - 10%, 0-10V: 100 - 3%
<b>Rated Life:</b>	50000 Hours
<b>Mounting:</b>	Heavy gauge retention clips support trim firmly. Safety cabling standard.
<b>Standards:</b>	ETL, cETL, Title 24 JA8-2016 Compliant Damp Location Listed
<b>Construction:</b>	Aluminum body with extruded acrylic diffuser



#### FINISHES



#### LINE DRAWING

